

PRESSURE GAUGES FOR WATER SYSTEMS

APPLICATION : For pumped water systems autoclaves etc.

SPECIFICATION : **Case :** ABS. **Window :** shatter resistant acrylic with adjustable red pointer. **Connection :** brass. **Sensitive element :** sealed alloy Bourdon tube. **Mechanism :** high precision watchmakers brass. **Joints :** soldered with tin alloy. **Dial :** stoved enamel on aluminium. **Accuracy :** class 2.5. **Scale :** dual bar (outer) + psi (inner).

PRICES : Please note that prices shown are the current list price for each gauge or product. OEM and re-seller discounts are available together with progressive quantity discounts.

50mm (2") diameter, Bottom connection, 1/4" BSP tapered thread, Scale : mH²O

Code 914 530 12	Range 16 mH ² O	£ 7.95	
Code 914 531 12	Range 25 mH ² O	£ 6.95	
Code 914 532 12	Range 40 mH ² O	£ 6.95	
Code 914 533 12	Range 60 mH ² O	£ 6.95	

50mm (2") diameter, Bottom connection, 1/4" BSP tapered thread, Scale : bar+psi

Code 904 530 15	Range 1,6 bar + psi	£ 7.25	
Code 904 531 15	Range 2,5 bar + psi	£ 6.25	
Code 904 532 15	Range 4 bar + psi	£ 6.25	
Code 904 533 15	Range 6 bar + psi	£ 6.25	
Code 904 534 15	Range 10 bar + psi	£ 6.25	
Code 904 535 15	Range 16 bar + psi	£ 6.25	

cewal UK LTD

Unit 4C • Woodhall Business Park • Sudbury • Suffolk • CO10 1WH

Tel: +44 (0) 1787 882038 • Fax: +44 (0) 1787 882039

Email: info@cewal.co.uk • Website: www.cewal.co.uk