

CAPSULE GAUGES - SCALED MILLIBAR BOTTOM CONNECTION - METAL CASED

APPLICATION : Measurement of low pressure. Particularly suited for gases that are not corrosive to copper or tin alloys.

SPECIFICATION : **Case :** stoved enamel on pressed steel. **Window :** shatter resistant acrylic. **Connection :** brass. **Sensitive element :** operation by the deflection of a copper beryllium bellows mechanically protected against over pressure. **Mechanism :** high precision watchmakers brass with zero adjustment. **Indicator :** anodised aluminium. **Dial :** stoved enamel on aluminium. **Accuracy :** class 1.6.

PRICES : Please note that prices shown are the current list price for each gauge or product. OEM and re-seller discounts are available together with progressive quantity discounts.

100mm (4") diameter, Connection : 1/2" BSP parallel, Scale : Millibar

Code 914 015 01	Range 40 mbar	£ 39.95
Code 914 015 02	Range 60 mbar	£ 39.95
Code 914 015 03	Range 100 mbar	£ 39.95
Code 914 015 04	Range 160 mbar	£ 39.95
Code 914 015 05	Range 250 mbar	£ 39.95
Code 914 015 06	Range 400 mbar	£ 39.95
Code 914 015 07	Range 600 mbar	£ 39.95



Please note

Back connection available for 63 mm and 100 mm diameter on request.

cewal UK LTD

Unit 4C • Woodhall Business Park • Sudbury • Suffolk • CO10 1WH

Tel: +44 (0) 1787 882038 • Fax: +44 (0) 1787 882039

Email: info@cewal.co.uk • Website: www.cewal.co.uk