

RIGID STEM THERMOMETER BOTTOM STEM - METAL CASED

APPLICATION : Suitable for heating, refrigeration and air conditioning systems and central heating and refrigeration equipment generally.

SPECIFICATION : **Case** : ABS. **Stem** : 9mm Ø brass tube. **Pocket** : brass 1/2" BSP tapered. **Window** : shatter resistant acrylic. **Dial** : stoved enamel on aluminium. **Movement** : operated by liquid expansion.

Please Note: Many popular H&V specification thermometers also available dual scale °C+°F with chrome bezel.

PRICES : Please note that prices shown are the current list price for each gauge or product. OEM and re-seller discounts are available together with progressive quantity discounts.

80mm diameter

Code 916 480 51	Range - 30 / + 50 °C	stem 5 cm	£ 20.95
Code 916 480 52	Range 0 / 60 °C	stem 5 cm	£ 20.95
Code 916 480 50	Range 0 / 120 °C	stem 5 cm	£ 20.95
Code 916 481 01	Range - 30 / + 50 °C	stem 10 cm	£ 22.25
Code 916 481 02	Range 0 / 60 °C	stem 10 cm	£ 22.25
Code 916 481 00	Range 0 / 120 °C	stem 10 cm	£ 22.25



STANDARD POCKETS

Standard pockets with 1/2" BSP tapered connection in brass.

Code 918 760 51	Pocket I.S.P.E.S.L	5 cm	£ 2.50
Code 918 761 01	Pocket I.S.P.E.S.L	10 cm	£ 3.25
Code 918 761 50	Pocket I.S.P.E.S.L	15 cm	£ 3.85
Code 918 762 00	Pocket I.S.P.E.S.L	20 cm	£ 4.35
Code 918 762 50	Pocket I.S.P.E.S.L	25 cm	£ 4.85
Code 918 763 00	Pocket I.S.P.E.S.L	30 cm	£ 5.40



cewal UK LTD

Unit 4C • Woodhall Business Park • Sudbury • Suffolk • CO10 1WH

Tel: +44 (0) 1787 882038 • Fax: +44 (0) 1787 882039

Email: info@cewal.co.uk • Website: www.cewal.co.uk